

**GigaDevice Semiconductor Inc.**

**GD32E231K-EVAL**

**Arm<sup>®</sup> Cortex<sup>®</sup>-M23 32-bit MCU**

## **User Guide**

Revision 1.0

(Dec. 2023)

# Table of Contents

<b>TABLE OF CONTENTS.....</b>	<b>1</b>
<b>LIST OF FIGURES .....</b>	<b>3</b>
<b>LIST OF TABLES .....</b>	<b>4</b>
<b>1. SUMMARY .....</b>	<b>5</b>
<b>2. FUNCTION PIN ASSIGN.....</b>	<b>5</b>
<b>3. GETTING STARTED .....</b>	<b>5</b>
<b>4. HARDWARE LAYOUT OVERVIEW .....</b>	<b>6</b>
4.1. Power supply .....	6
4.2. Boot option .....	6
4.3. LED .....	7
4.4. KEY .....	7
4.5. USART0 .....	7
4.6. ADC .....	8
4.7. I2S.....	8
4.8. I2C.....	8
4.9. SPI-FLASH .....	9
4.10. SPI-TFT LCD .....	9
4.11. CMP.....	10
4.12. OPA .....	10
4.13. GD-Link.....	11
4.14. Extension.....	11
4.15. MCU.....	12
<b>5. ROUTINE USE GUIDE .....</b>	<b>13</b>
5.1. GPIO_Running_LED .....	13
5.1.1. DEMO purpose .....	13
5.1.2. DEMO running result .....	13
5.2. GPIO_Key_Polling_mode.....	13
5.2.1. DEMO purpose .....	13
5.2.2. DEMO running result .....	13
5.3. EXTI_Key_Interrupt_mode .....	14
5.3.1. DEMO purpose .....	14
5.3.2. DEMO running result .....	14
5.4. USART_Printf.....	14
5.4.1. DEMO purpose .....	14
5.4.2. DEMO running result .....	14
5.5. USART_HyperTerminal_Interrupt.....	15

5.5.1.	DEMO purpose .....	15
5.5.2.	DEMO running result .....	15
<b>5.6.</b>	<b>USART_DMA .....</b>	<b>15</b>
5.6.1.	DEMO purpose .....	15
5.6.2.	DEMO running result .....	15
<b>5.7.</b>	<b>ADC_Conversion_Triggered_By_Timer .....</b>	<b>16</b>
5.7.1.	DEMO purpose .....	16
5.7.2.	DEMO running result .....	16
<b>5.8.</b>	<b>Comparator_Obtain_Brightness.....</b>	<b>16</b>
5.8.1.	DEMO purpose .....	16
5.8.2.	DEMO running result .....	17
<b>5.9.</b>	<b>I2C_EEPROM .....</b>	<b>17</b>
5.9.1.	DEMO purpose .....	17
5.9.2.	DEMO running result .....	17
<b>5.10.</b>	<b>SPI_FLASH .....</b>	<b>18</b>
5.10.1.	DEMO purpose .....	18
5.10.2.	DEMO running result .....	18
<b>5.11.</b>	<b>SPI_TFT_LCD_Driver .....</b>	<b>19</b>
5.11.1.	DEMO purpose .....	19
5.11.2.	DEMO running result .....	19
<b>5.12.</b>	<b>I2S_Audio_Player .....</b>	<b>20</b>
5.12.1.	DEMO purpose .....	20
5.12.2.	DEMO running result .....	20
<b>5.13.</b>	<b>RCU_Clock_Out .....</b>	<b>20</b>
5.13.1.	DEMO purpose .....	20
5.13.2.	DEMO running result .....	21
<b>5.14.</b>	<b>PMU_sleep_wakeup .....</b>	<b>21</b>
5.14.1.	DEMO purpose .....	21
5.14.2.	DEMO running result .....	21
<b>5.15.</b>	<b>RTC_Calendar .....</b>	<b>21</b>
5.15.1.	DEMO purpose .....	21
5.15.2.	DEMO running result .....	21
<b>5.16.</b>	<b>TIMER_Breath_LED.....</b>	<b>22</b>
5.16.1.	DEMO purpose .....	22
5.16.2.	DEMO running result .....	22
<b>6.</b>	<b>REVISION HISTORY .....</b>	<b>23</b>

# List of Figures

Figure 4-1 Schematic diagram of power supply.....	6
Figure 4-2 Schematic diagram of boot option .....	6
Figure 4-3 Schematic diagram of LED function .....	7
Figure 4-4 Schematic diagram of Key function .....	7
Figure 4-5 Schematic diagram of USART0 function .....	7
Figure 4-6 Schematic diagram of ADC function .....	8
Figure 4-7 Schematic diagram of I2S function .....	8
Figure 4-8 Schematic diagram of I2C function .....	8
Figure 4-9 Schematic diagram of SPI-FLASH function .....	9
Figure 4-10 Schematic diagram of SPI-TFT LCD function .....	9
Figure 4-11 Schematic diagram of CMP function.....	10
Figure 4-12 Schematic diagram of OPA function .....	10
Figure 4-13 Schematic diagram of GD-Link function.....	11
Figure 4-14 Schematic diagram of Extension Pin .....	11
Figure 4-15 Schematic diagram of MCU Pin .....	12

# List of Tables

Table 2-1 Pin assignment.....	5
Table 4-1 Boot configuration .....	6
Table 6-1 Revision history .....	23

## 1. Summary

GD32E231K-EVAL evaluation board uses GD32E231K8T6 as the main controller. As a complete development platform of GD32E231 powered by Arm® Cortex®-M23 core, the board supports full range of peripherals. It uses mini-USB interface to supply 5V power. GD-Link, Reset, Boot, User button key, LED, I2C, I2S, USART, TFT-LCD, IFRP LED、IFRP Transceiver, RTC, SPI, ADC and Extension Pin are also included. This document details its hardware schematic and the relevant applications.

## 2. Function Pin Assign

Table 2-1 Pin assignment

Function	Pin	Description
LED	PA8	LED1
RESET	NRST	K1-Reset
KEY	PA0	K2-Wakeup
	PC13	K3-Userkey
OPA	PA15	JP3_INPA
	PA14	JP3_INNA
	VOUTA	JP3_VOUTA
I2C	PB6	I2C0_SCL
	PB7	I2C0_SDA
I2S	PA4	I2S0_WS
	PA5	I2S0_CK
	PA7	I2S0_SD
	PA6	I2S0_MCK
USART0	PA9	USART0_TX
	PA10	USART0_RX
SPI	PB3	SPI0_SCK
	PB4	SPI0_MISO
	PB5	SPI0_MOSI
	PA12	SPIFlash_CS
	PB0	TFT_CS
	PB1	TFT_RESET
ADC	PA2	ADC_IN2
COMPARATOR	PA1	COMP0_INP

## 3. Getting started

The EVAL Board uses mini-USB connector to get power, the hardware system power is

+3.3V. A GD-Link on board is necessary in order to download and debug programs. Select the correct boot mode and then power on, the LEDPWR will turn on, which indicates that the power supply is OK.


There are Keil version and IAR version of all projects. Keil version of the projects are created based on Keil MDK-ARM 5.29 uVision5. IAR version of the projects are created based on IAR Embedded Workbench for ARM 8.32.1. During use, the following points should be noted:

1. If you use Keil uVision5 to open the project. In order to solve the "Device Missing (s)" problem, you can install GigaDevice.GD32E23x\_DFP.1.1.2.pack.
2. If you use IAR to open the project, install IAR\_GD32E23x\_ADDON\_1.2.2.exe to load the associated files.

## 4. Hardware layout overview

### 4.1. Power supply

Figure 4-1 Schematic diagram of power supply



### 4.2. Boot option

Figure 4-2 Schematic diagram of boot option





Table 4-1 Boot configuration

BOOT1	BOOT0	Boot Mode
Default	2-3	User memory
	1-2	System memory
Changed by ISP	1-2	SRAM memory


### 4.3. LED

Figure 4-3 Schematic diagram of LED function




### 4.4. KEY

Figure 4-4 Schematic diagram of Key function



### 4.5. USART0


Figure 4-5 Schematic diagram of USART0 function






## 4.6. ADC

Figure 4-6 Schematic diagram of ADC function




## 4.7. I2S

Figure 4-7 Schematic diagram of I2S function




## 4.8. I2C

Figure 4-8 Schematic diagram of I2C function




## 4.9. SPI-FLASH

Figure 4-9 Schematic diagram of SPI-FLASH function




## 4.10. SPI-TFT LCD

Figure 4-10 Schematic diagram of SPI-TFT LCD function




## 4.11. CMP

Figure 4-11 Schematic diagram of CMP function




## 4.12. OPA

Figure 4-12 Schematic diagram of OPA function




### 4.13. GD-Link

**Figure 4-13 Schematic diagram of GD-Link function**




#### 4.14. Extension

### Figure 4-14 Schematic diagram of Extension Pin



## 4.15. MCU

Figure 4-15 Schematic diagram of MCU Pin



## 5. Routine use guide

### 5.1. GPIO\_Running\_LED

#### 5.1.1. DEMO purpose

This Demo includes the following functions of GD32 MCU:

- Learn to use GPIO for controlling the LED.
- Learn to use SysTick to generate 1ms delay.

GD32E231K-EVAL board has one LED. The LED1 is controlled by GPIO. This demo will show how to light the LED1.

#### 5.1.2. DEMO running result

Download the program <01\_GPIO\_Running\_LED> to the EVAL board, LED1 will turn on every 1000ms, and then turn off. 1000ms later, the LED1 works like previous again.

### 5.2. GPIO\_Key\_Polling\_mode

#### 5.2.1. DEMO purpose

This Demo includes the following functions of GD32 MCU:

- Learn to use GPIO control the LED and the KEY.
- Learn to use SysTick to generate 1ms delay.

GD32E231K-EVAL board has three keys and one LED. The three keys are Reset key, Wakeup key and Userkey key. The LED1 is controlled by GPIO.

This demo will show how to use the Wakeup key to control the LED1. When press down the Wakeup Key, it will check the input value of the IO port. If the value is 1, wait for 100ms. Then check the input value of the IO port again. If the value is still 1, indicates that the button is pressed down successfully, and light the LED1.

#### 5.2.2. DEMO running result

Download the program <02\_GPIO\_Key\_Polling\_mode> to the EVAL board, when press down the Wakeup Key, LED1 will be turned on. Press down the Wakeup Key again, LED1 will be turned off.

## 5.3. EXTI\_Key\_Interrupt\_mode

### 5.3.1. DEMO purpose

This Demo includes the following functions of GD32 MCU:

- Learn to use GPIO to control the LED and the KEY
- Learn to use EXTI to generate external interrupt

GD32E231K-EVAL board has three keys and one LED. The three keys are Reset key, Wakeup key and User key. The LED1 are controlled by GPIO.

This demo will show how to use EXTI interrupt line to control the LED1. When press down the Wakeup Key, it will produce an interrupt. In the interrupt service function, the demo will toggle LED1.

### 5.3.2. DEMO running result

Download the program <03\_EXTI\_Key\_Interrupt\_mode> to the EVAL board, when press down the Wakeup Key, LED1 will be turned on. Press down the Wakeup Key again, LED1 will be turned off.

## 5.4. USART\_Printf

### 5.4.1. DEMO purpose

This Demo includes the following functions of GD32 MCU:

- Learn to retarget the C library printf function to the USART.

### 5.4.2. DEMO running result

Download the program <04\_USART\_Printf> to the EVAL board and run. serial port will output "usart printf test example!".

The information via a serial port output as following.

```
usart printf test example!
```

## 5.5. USART\_HyperTerminal\_Interrupt

### 5.5.1. DEMO purpose


This Demo includes the following functions of GD32 MCU:

- Learn to use the EVAL\_COM transmit and receive interrupts to communicate with the hyperterminal.

### 5.5.2. DEMO running result

Download the program <05\_USART\_HyperTerminal\_Interrupt> to the EVAL board and run. Firstly, the COM sends the “USART interrupt test” to the hyperterminal and waits for receiving data from the hyperterminal that you must send. The string that you have sent is stored in the receiver\_buffer array. The receive buffer have a receivesize=32 bytes as maximum. After that, compare rxcount with receivesize. If rxcount is same with receivesize, the COM sends the “USART receive successfully!” to the hyperterminal.

The information via a serial port output as following:



## 5.6. USART\_DMA

### 5.6.1. DEMO purpose

This Demo includes the following functions of GD32 MCU:

- Learn to use the COM transmit and receive using DMA.

### 5.6.2. DEMO running result

Download the program <06\_USART\_DMA> to the EVAL board and run. Firstly, the COM sends the “a usart dma function test example!

USART DMA receive and transmit example, please input 10 bytes:” to the hyperterminal and



then loops waiting for receiving max 10 datas from the hyperterminal. Every time if the number of data you enter is equalto or more than 10 bytes, USART will send 10 bytes to the hyperterminal.

The information via a serial port output as following:

```
a usart dma function test example!  
USART DMA receive and transmit example, please input 10 bytes:  
gfhgfhgdgf
```

## 5.7. ADC\_Conversion\_Triggered\_By\_Timer

### 5.7.1. DEMO purpose

This Demo includes the following functions of GD32 MCU:

- Learn to use ADC to convert analog to digital
- Learn to use TIMER to generate a channel compare event
- Learn to use LCD to show the ADC converted result

TIMER0 CH0 event triggers ADC conversion, the value displayed on the LCD corresponds to the ADC analog input, and changes with it. The converted data are moved to SRAM through DMA continuously.

### 5.7.2. DEMO running result

Download the program <07\_ADC\_Conversion\_Triggered\_By\_Timer> to the GD32E231K-EVAL board, adjust the adjustable potentiometer knob to change the analog input. The ADC, which is triggered by TIMER0 CH0 event, will convert the analog input, and you will see the result, a voltage curve, on the LCD. The curve adjusts with the analog input.

## 5.8. Comparator\_Obtain\_Brightness

### 5.8.1. DEMO purpose

This Demo includes the following functions of GD32 MCU:

- Learn to use comparator output compare result

The comparator has two inputs, in this demo, one input is PA1, and the other one is the reference voltage. Compare the two input voltages, the output is a high or low level, and the LED1 will performs the corresponding action.

### 5.8.2. DEMO running result

Download the program <08\_Comparator\_Obtain\_Brightness> to the EVAL board, comparing two input voltage, if output level is high, LED1 is on, otherwise LED1 is off.

## 5.9. I2C\_EEPROM

### 5.9.1. DEMO purpose

This Demo includes the following functions of GD32 MCU:

- Learn how to use the master transmitting mode of the I2C module.
- Learn how to use the master receiving mode of the I2C module.
- Learn to read and write the EEPROM with the I2C interface.

### 5.9.2. DEMO running result

Download the program <09\_I2C\_EEPROM> to the EVAL board and run. Connect serial cable to USART, and open the HyperTerminal to show the print message.

Firstly, the data of 256 bytes will be written to the EEPROM from the address 0x00 and printed by the serial port. Then, reading the EEPROM from address 0x00 for 256 bytes and the result will be printed. Finally, compare the data that were written to the EEPROM and the data that were read from the EEPROM. If they are the same, the serial port will output "I2C-AT24C02 test passed!" and the LED1 light starts flashing, otherwise the serial port will output "Err: data read and write aren't matching." and the LED1 keeps on.

The output information via the serial port is as following.

```
I2C-24C02 configured...

The I2C is hardware interface
The speed is 400K
AT24C02 writing...
0x00 0x01 0x02 0x03 0x04 0x05 0x06 0x07 0x08 0x09 0x0A 0x0B 0x0C 0x0D 0x0E 0x0F
0x10 0x11 0x12 0x13 0x14 0x15 0x16 0x17 0x18 0x19 0x1A 0x1B 0x1C 0x1D 0x1E 0x1F
0x20 0x21 0x22 0x23 0x24 0x25 0x26 0x27 0x28 0x29 0x2A 0x2B 0x2C 0x2D 0x2E 0x2F
0x30 0x31 0x32 0x33 0x34 0x35 0x36 0x37 0x38 0x39 0x3A 0x3B 0x3C 0x3D 0x3E 0x3F
0x40 0x41 0x42 0x43 0x44 0x45 0x46 0x47 0x48 0x49 0x4A 0x4B 0x4C 0x4D 0x4E 0x4F
0x50 0x51 0x52 0x53 0x54 0x55 0x56 0x57 0x58 0x59 0x5A 0x5B 0x5C 0x5D 0x5E 0x5F
0x60 0x61 0x62 0x63 0x64 0x65 0x66 0x67 0x68 0x69 0x6A 0x6B 0x6C 0x6D 0x6E 0x6F
0x70 0x71 0x72 0x73 0x74 0x75 0x76 0x77 0x78 0x79 0x7A 0x7B 0x7C 0x7D 0x7E 0x7F
0x80 0x81 0x82 0x83 0x84 0x85 0x86 0x87 0x88 0x89 0x8A 0x8B 0x8C 0x8D 0x8E 0x8F
0x90 0x91 0x92 0x93 0x94 0x95 0x96 0x97 0x98 0x99 0x9A 0x9B 0x9C 0x9D 0x9E 0x9F
0xA0 0xA1 0xA2 0xA3 0xA4 0xA5 0xA6 0xA7 0xA8 0xA9 0xAA 0xAB 0xAC 0xAD 0xAE 0xAF
0xB0 0xB1 0xB2 0xB3 0xB4 0xB5 0xB6 0xB7 0xB8 0xB9 0xBA 0xBB 0xBC 0xBD 0xBE 0xBF
0xC0 0xC1 0xC2 0xC3 0xC4 0xC5 0xC6 0xC7 0xC8 0xC9 0xCA 0xCB 0xCC 0xCD 0xCE 0xCF
0xD0 0xD1 0xD2 0xD3 0xD4 0xD5 0xD6 0xD7 0xD8 0xD9 0xDA 0xDB 0xDC 0xDD 0xDE 0xDF
0xE0 0xE1 0xE2 0xE3 0xE4 0xE5 0xE6 0xE7 0xE8 0xE9 0xEA 0xEB 0xEC 0xED 0xEE 0xEF
0xF0 0xF1 0xF2 0xF3 0xF4 0xF5 0xF6 0xF7 0xF8 0xF9 0xFA 0xFB 0xFC 0xFD 0xFE 0xFF
AT24C02 reading...
0x00 0x01 0x02 0x03 0x04 0x05 0x06 0x07 0x08 0x09 0x0A 0x0B 0x0C 0x0D 0x0E 0x0F
0x10 0x11 0x12 0x13 0x14 0x15 0x16 0x17 0x18 0x19 0x1A 0x1B 0x1C 0x1D 0x1E 0x1F
0x20 0x21 0x22 0x23 0x24 0x25 0x26 0x27 0x28 0x29 0x2A 0x2B 0x2C 0x2D 0x2E 0x2F
0x30 0x31 0x32 0x33 0x34 0x35 0x36 0x37 0x38 0x39 0x3A 0x3B 0x3C 0x3D 0x3E 0x3F
0x40 0x41 0x42 0x43 0x44 0x45 0x46 0x47 0x48 0x49 0x4A 0x4B 0x4C 0x4D 0x4E 0x4F
0x50 0x51 0x52 0x53 0x54 0x55 0x56 0x57 0x58 0x59 0x5A 0x5B 0x5C 0x5D 0x5E 0x5F
0x60 0x61 0x62 0x63 0x64 0x65 0x66 0x67 0x68 0x69 0x6A 0x6B 0x6C 0x6D 0x6E 0x6F
0x70 0x71 0x72 0x73 0x74 0x75 0x76 0x77 0x78 0x79 0x7A 0x7B 0x7C 0x7D 0x7E 0x7F
0x80 0x81 0x82 0x83 0x84 0x85 0x86 0x87 0x88 0x89 0x8A 0x8B 0x8C 0x8D 0x8E 0x8F
0x90 0x91 0x92 0x93 0x94 0x95 0x96 0x97 0x98 0x99 0x9A 0x9B 0x9C 0x9D 0x9E 0x9F
0xA0 0xA1 0xA2 0xA3 0xA4 0xA5 0xA6 0xA7 0xA8 0xA9 0xAA 0xAB 0xAC 0xAD 0xAE 0xAF
0xB0 0xB1 0xB2 0xB3 0xB4 0xB5 0xB6 0xB7 0xB8 0xB9 0xBA 0xBB 0xBC 0xBD 0xBE 0xBF
0xC0 0xC1 0xC2 0xC3 0xC4 0xC5 0xC6 0xC7 0xC8 0xC9 0xCA 0xCB 0xCC 0xCD 0xCE 0xCF
0xD0 0xD1 0xD2 0xD3 0xD4 0xD5 0xD6 0xD7 0xD8 0xD9 0xDA 0xDB 0xDC 0xDD 0xDE 0xDF
0xE0 0xE1 0xE2 0xE3 0xE4 0xE5 0xE6 0xE7 0xE8 0xE9 0xEA 0xEB 0xEC 0xED 0xEE 0xEF
0xF0 0xF1 0xF2 0xF3 0xF4 0xF5 0xF6 0xF7 0xF8 0xF9 0xFA 0xFB 0xFC 0xFD 0xFE 0xFF
I2C-AT24C02 test passed!
```

## 5.10. SPI\_FLASH

### 5.10.1. DEMO purpose

This demo includes the following functions of GD32 MCU:

- Learn to use the SPI mode of SPI unit to read and write NOR Flash with the SPI interface

### 5.10.2. DEMO running result

The computer serial port line connected to the COM port of development board, set the baud rate of HyperTerminal software to 115200, 8 bits data bit, 1 bit stop bit.

Download the program <10\_QSPI\_FLASH> to the EVAL board, the HyperTerminal software can observe the operation condition and will display the ID of the flash, 256 bytes data which are written to and read from flash. Compare the data that were written to the flash and the

data that were read from the flash. If they are the same, the serial port will output “SPI-GD25Q16 Test Passed!”, otherwise, the serial port will output “Err: Data Read and Write aren’t Matching.”. At last, toggle the LED1 every 500ms. The following is the experimental results.

```
#####
GD32E231K_EVAL_1.0 System is Starting up...
GD32E231K_EVAL_1.0 Flash:64K
GD32E231K_EVAL_1.0 The CPU Unique Device ID:[FFFFFFFF-FFFFFFFF-FFFFFFFF]
GD32E231K_EVAL_1.0 SPI Flash:GD25Q16 configured...
The Flash_ID:0xC84015

Write to tx_buffer:
0x00 0x01 0x02 0x03 0x04 0x05 0x06 0x07 0x08 0x09 0x0A 0x0B 0x0C 0x0D 0x0E 0x0F 0x10 0x11 0x12 0x13 0x14 0x15 0x16
0x17 0x18 0x19 0x1A 0x1B 0x1C 0x1D 0x1E 0x1F 0x20 0x21 0x22 0x23 0x24 0x25 0x26 0x27 0x28 0x29 0x2A 0x2B 0x2C 0x2D
0x2E 0x2F 0x30 0x31 0x32 0x33 0x34 0x35 0x36 0x37 0x38 0x39 0x3A 0x3B 0x3C 0x3D 0x3E 0x3F 0x40 0x41 0x42 0x43 0x44
0x45 0x46 0x47 0x48 0x49 0x4A 0x4B 0x4C 0x4D 0x4E 0x4F 0x50 0x51 0x52 0x53 0x54 0x55 0x56 0x57 0x58 0x59 0x5A 0x5B
0x5C 0x5D 0x5E 0x5F 0x60 0x61 0x62 0x63 0x64 0x65 0x66 0x67 0x68 0x69 0x6A 0x6B 0x6C 0x6D 0x6E 0x6F 0x70 0x71 0x72
0x73 0x74 0x75 0x76 0x77 0x78 0x79 0x7A 0x7B 0x7C 0x7D 0x7E 0x7F 0x80 0x81 0x82 0x83 0x84 0x85 0x86 0x87 0x88 0x89
0x8A 0x8B 0x8C 0x8D 0x8E 0x8F 0x90 0x91 0x92 0x93 0x94 0x95 0x96 0x97 0x98 0x99 0x9A 0x9B 0x9C 0x9D 0x9E 0x9F 0xA0
0xA1 0xA2 0xA3 0xA4 0xA5 0xA6 0xA7 0xA8 0xA9 0xAA 0xAB 0xAC 0xAD 0xAE 0xAF 0xB0 0xB1 0xB2 0xB3 0xB4 0xB5 0xB6 0xB7
0xB8 0xB9 0xBA 0xBB 0xBC 0xBD 0xBE 0xBF 0xC0 0xC1 0xC2 0xC3 0xC4 0xC5 0xC6 0xC7 0xC8 0xC9 0xCA 0xCB 0xCC 0xCD 0xCE
0xCF 0xD0 0xD1 0xD2 0xD3 0xD4 0xD5 0xD6 0xD7 0xD8 0xD9 0xDA 0xDB 0xDC 0xDD 0xDE 0xDF 0xE0 0xE1 0xE2 0xE3 0xE4 0xE5
0xE6 0xE7 0xE8 0xE9 0xEA 0xEB 0xEC 0xED 0xEE 0xEF 0xF0 0xF1 0xF2 0xF3 0xF4 0xF5 0xF6 0xF7 0xF8 0xF9 0xFA 0xFB 0xFC
0xFD 0xFE 0xFF

Read from rx_buffer:
0x00 0x01 0x02 0x03 0x04 0x05 0x06 0x07 0x08 0x09 0x0A 0x0B 0x0C 0x0D 0x0E 0x0F 0x10 0x11 0x12 0x13 0x14 0x15 0x16
0x17 0x18 0x19 0x1A 0x1B 0x1C 0x1D 0x1E 0x1F 0x20 0x21 0x22 0x23 0x24 0x25 0x26 0x27 0x28 0x29 0x2A 0x2B 0x2C 0x2D
0x2E 0x2F 0x30 0x31 0x32 0x33 0x34 0x35 0x36 0x37 0x38 0x39 0x3A 0x3B 0x3C 0x3D 0x3E 0x3F 0x40 0x41 0x42 0x43 0x44
0x45 0x46 0x47 0x48 0x49 0x4A 0x4B 0x4C 0x4D 0x4E 0x4F 0x50 0x51 0x52 0x53 0x54 0x55 0x56 0x57 0x58 0x59 0x5A 0x5B
0x5C 0x5D 0x5E 0x5F 0x60 0x61 0x62 0x63 0x64 0x65 0x66 0x67 0x68 0x69 0x6A 0x6B 0x6C 0x6D 0x6E 0x6F 0x70 0x71 0x72
0x73 0x74 0x75 0x76 0x77 0x78 0x79 0x7A 0x7B 0x7C 0x7D 0x7E 0x7F 0x80 0x81 0x82 0x83 0x84 0x85 0x86 0x87 0x88 0x89
0x8A 0x8B 0x8C 0x8D 0x8E 0x8F 0x90 0x91 0x92 0x93 0x94 0x95 0x96 0x97 0x98 0x99 0x9A 0x9B 0x9C 0x9D 0x9E 0x9F 0xA0
0xA1 0xA2 0xA3 0xA4 0xA5 0xA6 0xA7 0xA8 0xA9 0xAA 0xAB 0xAC 0xAD 0xAE 0xAF 0xB0 0xB1 0xB2 0xB3 0xB4 0xB5 0xB6 0xB7
0xB8 0xB9 0xBA 0xBB 0xBC 0xBD 0xBE 0xBF 0xC0 0xC1 0xC2 0xC3 0xC4 0xC5 0xC6 0xC7 0xC8 0xC9 0xCA 0xCB 0xCC 0xCD 0xCE
0xCF 0xD0 0xD1 0xD2 0xD3 0xD4 0xD5 0xD6 0xD7 0xD8 0xD9 0xDA 0xDB 0xDC 0xDD 0xDE 0xDF 0xE0 0xE1 0xE2 0xE3 0xE4 0xE5
0xE6 0xE7 0xE8 0xE9 0xEA 0xEB 0xEC 0xED 0xEE 0xEF 0xF0 0xF1 0xF2 0xF3 0xF4 0xF5 0xF6 0xF7 0xF8 0xF9 0xFA 0xFB 0xFC
0xFD 0xFE 0xFF
SPI-GD25Q16 Test Passed!
```

## 5.11. SPI\_TFT\_LCD\_Driver

### 5.11.1. DEMO purpose

This Demo includes the following function of GD32 MCU:

- Learn how to use SPI to drive TFT LCD screen and display

GD32E231K-EVAL board has a TFT LCD screen which supports SPI interface. In this demo, tests of font, number, draw and color are displayed on the LCD screen respectively.

### 5.11.2. DEMO running result

Download the program <11\_SPI\_TFT\_LCD\_Driver> to the EVAL board. The LED1 is turned on and then turned off for test. After that, the LCD screen on the board will display the GUI tests in infinite loop.



## 5.12. I2S\_Audio\_Player

### 5.12.1. DEMO purpose

This Demo includes the following functions of GD32 MCU:

- Learn to use I2S module to output audio file

GD32E231K-EVAL board integrates the I2S (Inter-IC Sound) module, and the module can communicate with external devices using the I2S audio protocol. This Demo mainly shows how to use the I2S interface of the board for audio output.

### 5.12.2. DEMO running result

Download the program <12\_I2S\_Audio\_Player>. After downloading the program, insert the earphone into the audio port J1, then listen to the audio file.

## 5.13. RCU\_Clock\_Out

### 5.13.1. DEMO purpose

This Demo includes the following functions of GD32 MCU:

- Learn to use GPIO control the LED
- Learn to use EXTI to generate external interrupt
- Learn to use the clock output function of RCU
- Learn to communicate with PC by USART

### 5.13.2. DEMO running result

Download the program <13\_RCU\_Clock\_Out> to the EVAL board and run. Connect serial cable to USART, open the HyperTerminal. When the program is running, HyperTerminal will display the initial information. Then user can choose the type of the output clock by pressing the User key. After pressing, the LED will be lit and HyperTerminal will display which mode be selected. The frequency of the output clock can be observed through the oscilloscope by PA8 pin.

Information via a serial port output as following:

```
/===== GigaDevice Clock output Demo =====/  
press User key to select clock output source  
CK_OUT: system clock  
CK_OUT: IRC6M  
CK_OUT: IRC28M  
CK_OUT: IRC40K  
CK_OUT: HXTAL  
CK_OUT: PLL/2
```

## 5.14. PMU\_sleep\_wakeup

### 5.14.1. DEMO purpose

This Demo includes the following functions of GD32 MCU:

- Learn to use the USART receive interrupt to wake up the PMU from sleep mode.

### 5.14.2. DEMO running result

Download the program < 14\_PMU\_sleep\_wakeup > to the EVAL board, connect serial cable to USART. After power-on, LED1 is off. The MCU will enter sleep mode and the software stops running. When the USART0 receives a byte of data from the HyperTerminal, the MCU will wake up from a receive interrupt. And LED1 will flash.

## 5.15. RTC\_Calendar

### 5.15.1. DEMO purpose

This Demo includes the following functions of GD32 MCU:

- Learn to use RTC module to implement calendar function
- Learn to use LCD module to display the time of calendar

### 5.15.2. DEMO running result

Download the program <15\_RTC\_Calendar> to the EVAL board and run. When the

program is running, the LED1 turn on, then turn off. And then the LCD prints out the information of the board, and the calendar. When you press the Wakeup key, the time will be configured to 2018-05-13, 12:00:00.

## **5.16. TIMER\_Breath\_LED**

### **5.16.1. DEMO purpose**

This Demo includes the following functions of GD32 MCU:

- Learn to use Timer output PWM wave
- Learn to update channel value

### **5.16.2. DEMO running result**

Download the program <16\_TIMER\_Breath\_LED> to the GD32E231K-EVAL board and run. PA8 should not be reused by other peripherals.

When the program is running, you can see LED1 lighting from dark to bright gradually and then gradually darken, ad infinitum, just like breathing as rhythm.

## 6. Revision history

Table 6-1 Revision history

Revision No.	Description	Date
1.0	Initial Release	Dec. 18, 2023



## Important Notice

This document is the property of GigaDevice Semiconductor Inc. and its subsidiaries (the "Company"). This document, including any product of the Company described in this document (the "Product"), is owned by the Company under the intellectual property laws and treaties of the People's Republic of China and other jurisdictions worldwide. The Company reserves all rights under such laws and treaties and does not grant any license under its patents, copyrights, trademarks, or other intellectual property rights. The names and brands of third party referred thereto (if any) are the property of their respective owner and referred to for identification purposes only.

The Company makes no warranty of any kind, express or implied, with regard to this document or any Product, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. The Company does not assume any liability arising out of the application or use of any Product described in this document. Any information provided in this document is provided only for reference purposes. It is the responsibility of the user of this document to properly design, program, and test the functionality and safety of any application made of this information and any resulting product. Except for customized products which has been expressly identified in the applicable agreement, the Products are designed, developed, and/or manufactured for ordinary business, industrial, personal, and/or household applications only. The Products are not designed, intended, or authorized for use as components in systems designed or intended for the operation of weapons, weapons systems, nuclear installations, atomic energy control instruments, combustion control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, life-support devices or systems, other medical devices or systems (including resuscitation equipment and surgical implants), pollution control or hazardous substances management, or other uses where the failure of the device or Product could cause personal injury, death, property or environmental damage ("Unintended Uses"). Customers shall take any and all actions to ensure using and selling the Products in accordance with the applicable laws and regulations. The Company is not liable, in whole or in part, and customers shall and hereby do release the Company as well as its suppliers and/or distributors from any claim, damage, or other liability arising from or related to all Unintended Uses of the Products. Customers shall indemnify and hold the Company as well as its suppliers and/or distributors harmless from and against all claims, costs, damages, and other liabilities, including claims for personal injury or death, arising from or related to any Unintended Uses of the Products.

Information in this document is provided solely in connection with the Products. The Company reserves the right to make changes, corrections, modifications or improvements to this document and Products and services described herein at any time, without notice.